Shared Display Wall Based Collaboration Environment in the Control Room of the DIII-D National Fusion Facility

Presented by Gheni Abla

Workshop on Advanced Collaborative Environments (WACE 05)

Seattle, Washington

Sep. 8-9, 2005





Acknowledgments

- The Staff of the DIII-D National Fusion Facility
 - DIII-D funded by DOE/OFES operated by General Atomics
- The National Fusion Collaboratory Project Team
 - Members: ANL, GA, LBL, MIT, PPPL, PCS, Utah
 - DOE Office of Advanced Scientific Computing Research






















Presentation's key points

- Fusion energy research experiments are time critical team effort
 - 20-50 people participate in each experiment
 - Intensive 20-30 minute data analysis & decision cycle
 - Data and analysis process and codes becoming complex too
 - Worldwide effort leading to ITER
- US DIII-D National Fusion Facility is using many collaboration tools
 - A variety of hardware and software collaboration tools in use
- Large Format Shared Display Wall System is being used
 - Displays real-time information about experiment and group activity
 - Enables data analysis result sharing among researchers
 - Facilitates large screen space for video conferencing tools
- Shared Display Wall deployment is success and more work needed





Fusion research seeks deployment of environmentally and economically attractive power plant




- Fusion: combining two light atoms into one atom
 - A nuclear reaction
 - Energy released
- A very hot reaction: plasma
- Fueled by Hydrogen
- High energy density
 - Pickup truck fusion fuel = 21,000 railcars of coal

Fusion is the energy source of sun





Three large U.S experimental facilities and a vibrant theoretical community








Current trends of fusion research

Fusion experiments growing in size and complexity

- Number of diagnostics constantly increasing
- Acquired data is getting larger
- Data analysis involving a larger group of people

Number of fusion facilities decreasing

- ITER- the next generation fusion experiment device will be built in France.
- Long term relocation of US Fusion program is not reasonable.
- Scientists need to work remotely








Fusion experiments are time critical operations

- Fusion experiments consist of a series of pulses, or "shots"
- A "shot" is when you turn on the device for a few seconds
- Take a shot, analyze results, plan next shot, set new device parameters, take next shot...
- Repeated in every ~20 minutes time







Both local and remote collaborations are critical for successful experiment

Experiment control room is complex environment

- 20-50 people work towards common goal
- Team consists of scientists, engineers, technicians, computer scientists
- Group-activity awareness and collaboration are critical

Experiment team also includes remote participants


- There are only several fusion experimental devices worldwide
- Scientists are geographically dispersed
- Need to access experimental data and participate discussions
- Collaboration between remote parties also important





Various tools deployed to support fusion research collaborations

- U.S. National Fusion Collaboratory (NFC) project is building advanced collaborative environment for fusion research
- Grid-based computation and collaboration services for experiment & simulation
 - Security
 - Visualization
 - Team collaboration within the control room
 - Remote participation




- NFC deployed software tools to support control room collaborations
 - Secure Data Management System & Remote computing
 - Access Grid
 - Instant Messaging
 - Large Format Shared Display Wall System





Shared display walls enhance the collaboration within the control room

- Shared display has high pixel resolution
 - Can display multiple visual information that normally doesn't fit in a normal computer screen
 - Capable of presenting multiple aspects of experimental activity
- Shared display provides large visual space
 - Presented information visible for all team members at control room
- Challenge is in software development that matches the need of control room
 - -"what to display"
 - -"how to display"







Shared display walls installed at fusion control rooms

NSTX



DIII-D

C-Mod







Shared display wall deployment at DIII-D control room

- 150-inch (3840 X 1024 pixel) large display
- Deployment is two step process
 - Identify experiment related critical info
 that is common interest of majority
 team members



- Develop new tools or customize existing tools for the shared display environment
- Deployed shared display wall software tools
 - Visualization tools that provide up-to-date information about experiment status
 - Data analysis results sharing tools that enable researchers move the information from desktop screen to large format shared display
 - Remote participation and video conferencing tools





Visualization tools for experiment status update

- Provide real-time info about experiment status and group activity
- Tool 1: Plasma shape movie player
- based on time-variable data
- automatically generates plasma shape animation of the newest pulse
- data update triggered by MDSplus events








Visualization tools for experiment status update (2)

Tool 2: Electronic log ticker application

- Displays pulse information and experiment comments as a scrolling text
- Data is read from relational data base
- Information update is triggered by MDSplus events

240parlA CIII (465 nm) 8x 2 ms R5/8.6 GA = 1.0 yes/no Comments: Tape time 11:24 good data







Visualization tools for experiment status update (2)

Tool 3: Data Analysis Monitor (DAM) status reporter

- Analyzes between-pulse data analysis status on real time
- Generates detailed status report
- The shared display wall version of the report organized by large categories. Information is color coded:





In progress

Data Storage System












Dispatch System



Data analysis results sharing system

- Captures the visualization window on user's screen as an image and displays on shared display wall
 - Integrated into IDL based visualization library-GAPlotObj as a menu item
- Snapshot of visualization window can be sent by choosing the "Send to Tiled Wall" menu item
- Works with standard data analysis tools based
 GAPlotObj visualization-plotting library
- Also integrated into "Toolbar" application (TCL/Tk)
- Captures a user specified region on the user's desktop screen & displays it on the shared display
- Shared image on the display wall can be saved by other users





Dump the Shared Info. on Tiled Wall

print (b&w)

print (w&b)

print (grey)

print (color)

preferences

redecorate


dismiss






VNC-based data analysis sharing system

- Allows users to share dynamic content from their workstation display.
- Based on a modified VNC protocol which shares individual windows rather than the entire desktop.
- Shared windows can be positioned independent of one-another on the shared display.










Simultaneous user interaction on the shared display

- Each user is assigned their own uniquely colored cursor.
- When user drags mouse off the edge of his workstation screen, it appears on the shared display.
- Users can simultaneously give mouse and keyboard input to applications on the shared display.
- Multi-cursor capability is implemented within a modified window manager by time-slicing the system cursor.







key events pass through

Using shared display wall system for remote participation

- Video streams of Access Grid and VRVS from remote sites displayed
- Life sized video of remote participant gave a realistic impression






- Controllable camera is for monitoring the shared display and control room
 - Remote participants can control (Pan/Tilt/Zoom) through the web
 - Example: Remote scientist in UK shared his screen snapshot image to the wall and then used camera to make sure his image was displayed correctly





A screen capture of the DIII-D shared display wall



Electronic log ticker application





Learned lessons

- GUI based desktop apps are not necessarily usable on shared display:
 GUI layout, color, font, cursor needs to be customized
- Collaboration tools need to be easy to use and should not request extra effort
- Not all of the tools from computer science labs directly work for control room environment.
- Location and size of the shared display and lighting in the control need carefully planned.





Results and Future Work

- Shared display wall has been utilized during the last experiment campaign
 - Public presentation space for experiment status and group activity
 - Large "white board" space for information sharing
 - Large screen for displaying video of remote participant
 - Deployment has been an iterative process
- Final results have been well received by the experimental team
- More work needs to be done in the next step
 - Increase the usability
 - Integrate with other new collaboration technologies.
 - E.g, Instant Messaging, a service of Access Grid
 - Web-based streaming to remote participants
 - More flexible controlling mechanism



